## MusicRainbow: A New User Interface to Discover Artists Using Audio-based Similarity and Web-based Labeling



#### Elias Pampalk and Masataka Goto

National Institute of Advanced Industrial Science and Technology (AIST) IT, AIST, 1-1-1 Umezono, Tsukuba, Ibaraki 305-8568, Japan



**MusicRainbow** is a simple user interface for browsing music collections. The colors of the rainbow encode different styles of music. Similar artists are located near each other on the circular rainbow. Labels are extracted from web pages to summarize the contents. The user controls the interface with a

knob which can be turned (to select a different artist) and pushed (to listen to music from the selected artist).

### Technique

To compute the similarity of artists we compare their songs using audio-based techniques which analyze loudness fluctuations and spectral shapes [1].







The distance between artists X and Y is computed by finding the closest song to each song (red & blue lines), computing the mean of the red lines and the mean of For each artist we retrieve related pages using Google [3]. The pages are parsed for words listed in one of three vocabularies and word occurrences are counted. Each

the blue lines, and taking the maximum of the two values.



The distances between artists define a similarity space. For our demonstration we use a collection consisting of 558 art-ists.

# vocabulary covers a different hierarchical level.



For each artist/word pair, we compute a relevance weight on the basis of the word occurances in the webpages [4].

1x Beats

•••



The shortest path which connects all artists is found using a travelling salesman algorithm [2].



The weights are smoothed. This helps identify labels which are useful to describe not only a single artist but a region on the rainbow. The peaks are used by a heuristic to decide where to place the labels.



The path in the high-dimensional similarity space is projected onto a circle. Each artist is assigned one position on the circle. Similar artists are located close to each other.



The smoothed weights of the labels placed inside the rainbow define the color intensities. Red corresponds to the most frequent term, purple to the least frequent.



E. Pampalk, Computational Models of Music Similarity and their Application in Music Information Retrieval, Doctoral Dissertation, Vienna University of Technology, Austria, 2006.
T. Pohle, E. Pampalk, and G. Widmer, Generating Similarity-Based Playlists Using Travelling Salesman Algorithms, in Proceedings of DAFx, 2005.
B. Whitman and S. Lawrence, Inferring Descriptions and Similarity for Music from Community Metadata, in Proceedings of ICMC, 2002.
K. Lagus and S. Kaski, Keyword Selection Method for Characterizing Text Document Maps, in Proceedings of ICANN, 1999.

#### Presented at the ISMIR International Conference on Music Information Retrieval, 8-12 October 2006, Victoria, Canada. This work was supported by CrestMuse, CREST, JST.